

MODEL 15 / SCISSOR-LIFT PODIUM ASSEMBLY INSTRUCTIONS

THANK YOU FOR PURCHASING
THE NEWEST JARVIS MARCHING
BAND PODIUM!

ASSEMBLY INSTRUCTIONS

1. INSTALL THE TONGUE USING THE 5/16" FASTENERS SUPPLIED.
2. INSTALL THE FOUR WHEELS. THE NON-SWIVEL WHEELS ARE TO BE INSTALLED ON END OPPOSITE THE TONGUE. (REST END OF PODIUM ON ELEVATED SUPPORT.)
3. INSTALL THE RAILING.
4. ASSEMBLY IS COMPLETE. THE PODIUM CAN NOW BE PULLED.

USAGE

1. BEFORE LIFTING, LOCK THE TWO NON-SWIVEL WHEELS.
2. TURN THE TWO LOCKING PLUNGER LEVERS 180 DEGREES OR UNTIL THE LEVER IS IN THE PLUNGER SLOT. THE PLATFORM WILL AUTOMATICALLY LOCK WHEN THE PLATFORM IS RAISED.
3. PLATFORM CAN NOW BE RAISED. ASSURE THAT PLATFORM IS LOCKED BY PULLING DOWN ON PLATFORM.
4. POSITION THE LADDER HOOKS ON THE ROUND CROSS BAR. PLATFORM CAN NOW BE USED.



Model 15

TO LOWER PLATFORM

1. PULL UP ON THE TWO LOCKING PLUNGERS AND ROTATE THE LEVER 180 DEGREES OR UNTIL THE LEVER IS 180 DEGREES OPPOSITE SLOT IN PLUNGER. STAY CLEAR OF PLATFORM WHILE DISENGAGING LOCKS.
2. HOLD UP ON PLATFORM WHILE DISENGAGING PLUNGERS. TO ASSURE IT WILL NOT FALL, SLOWLY PULL DOWN ON PLATFORM UNTIL IT IS FULLY RETRACTED.
3. UNLOCK WHEELS. PLATFORM CAN NOW BE PULLED.